

Engineer: Jack Curtis	Date: 4/22/04				
Drawn: Jack Curtis	Date: 4/22/04				
Approved: CTS	Date: 4/22/04				
Issued/ Revised	Date: 4/22/04	Size: A	Dwg. #: <b>5961-271212-APP</b>	Rev: <b>A</b>	Sheet: 1 Of 1

**Raytheon**

**JPS Communications**  
5800 Departure Drive, Raleigh, NC 27616

**APPLIES TO:** Motorola Spectra Consolette Radio

**RADIO MODIFICATIONS:** None required.

**RADIO PROGRAMMING:**

1. Console radios should normally be programmed for low transmit power.

**RADIO CONTROLS:**

1. Adjust the Volume Control until the yellow "SIGNAL" indicator on the associated DSP Module flashes with receive audio.

**CABLING:**

Standard ACU-1000 and ACU-T Interface cables are made up of a 2 foot TRP Radio Tray Interface cable and the appropriate 13-foot Extension cable.

ACU-1000 Interface Cable	JPS P/N 5961-291212	(5961-271212 + 5961-261002-00)
ACU-T Interface Cable	JPS P/N 5961-281212	(5961-271212 + 5961-281013-00)
TRP-1000 Shelf Interface Cable	JPS P/N 5961-271212	
Radio RF Connector Type		

**DSP PROGRAMMING:** (See Notes)

RX Level	3*	0dBm*
TX Level	6*	0dBm*
Squelch Type	VOX*	
COR Polarity	Active Low*	
High Frequency Equalizer	4*	Flat*
RX Audio Delay	2*	100 ms*
TX Audio Delay (Radio Type)	0*	No Delay*
Noise Reduction Value	0*	Off*
VOX/VMR Threshold	1*	Med1*
VOX/VMR Hang Time	3*	775 ms*
COR Inhibit After PTT	1*	100 ms*
All Others		As needed


(\* Indicates Default Value)

**NOTES:**

Raytheon JPS Communications has not developed specific settings for this model of radio. Use the generic DSP Setup Procedure to optimize the default values.

# PURCHASED PART

Rev	ECO	Date
A		



COMPONENT PCB  
(JPS P/N 5961-271000)

JU1  
JU2  
JU4


USED WITH:  
MOTOROLA SPECTRA CONSOLETTE

NOTE: SHIELD DRAIN CONNECTED TO PIN 1 OF P1 ONLY.

Designed By:	CTS	<b>Raytheon JPS Communications</b> Raleigh, NC USA		
Drawn By:	EDV	Title	CABLE, CPC TO MOTOROLA SPECTRA CONSOLETTE	
Checked By:	JAC	Size	Document Number	Rev
		A	<b>5961-271212</b>	A
		Issued Date	NOVEMBER 18, 2003	Sheet 1 of 1

# PURCHASED PART

Rev	ECO	Date
A		



NOTES: 1) USE BELDEN 9934 SHIELDED CABLE.  
2) CONNECT SHIELD DRAIN TO SHELL OF P1 ONLY.  
3) CONNECTORS P1 AND P2 MUST BE MOLDED TO THE CABLE.  
4) CABLE MUST BE LABELED WITH THE RAYTHEON/JPS P/N AND  
REV, VENDOR CODE AND DATE (MM/YY).


Designed By: JAC	<b>Raytheon JPS Communications</b>		
Drawn By: JAC	Title	CABLE, ACU-1000 RADIO EXTENSION - 13 FT	
Checked By: RBP	Size A	Document Number <b>5961-261002-00</b>	Rev A
	Issued Date JANUARY 5, 2004	Sheet <u>1</u> of <u>1</u>	

Rev	ECO	Date
A		

## PURCHASED PART

CONNECTOR AMP P/N 206708-1  
(JPS P/N 0362-005003)  
FEMALE PIN AMP P/N 1-66105-8  
(JPS P/N 0362-005002)

CONNECTOR AMP P/N 206705-4  
(JPS P/N 0362-009001)  
MALE PIN AMP P/N 1-66103-7  
(JPS P/N 0847-000011)



NOTES:

- 1) USE BELDEN 9934 SHIELDED CABLE.
- 2) CONNECT SHIELD DRAIN TO PIN 1 OF P1 ONLY.
- 3) CONNECTORS P1 AND P2 MUST BE MOLDED TO THE CABLE.
- 4) CABLE MUST BE LABELED WITH THE RAYTHEON/JPS P/N AND REV, VENDOR CODE AND DATE (MM/YY).

Designed By:	JAC	<b>Raytheon JPS Communications</b> Raleigh, NC USA		
Drawn By:	JAC	Title CABLE, ACU-T RADIO EXTENSION - 13 FT		
Checked By:	RBP	Size A	Document Number <b>5961-281013-00</b>	Rev A
		Issued Date JANUARY 5, 2004	Sheet <u>1</u> of <u>1</u>	